

MAINLAND FASTENERS

MINI CATALOGUE

sales@mainlandfasteners.co.nz

03 366 5590

Drop In Anchors CFDIA...



Medium Duty internally threaded anchor for shallow embedment applications in concrete and hard natural stone. Commonly used for anchoring threaded rods for the suspension of pipe work and sprinkler supports.

- Simple expansion with hammer blows.
- Can be flush set.
- Shallow embedment depth reduces clashes with reinforcement steel.
- Suitable for use with bolts or threaded rods of any length.
- Can be loaded immediately after installation.
- Available in Zinc Plate and Stainless Steel.
- Can be deep set below concrete surface.

Diameter	Drill Diameter	Yellow Zinc	Stainless Steel	Minimum Hole Depth	Thread Size
6.0mm x 25mm	8.0mm	•	•	25mm	6mm
8.0mm x 30mm	10.0mm	•	•	30mm	8mm
10.0mm x 40mm	12.0mm	•	•	40mm	10mm
12.0mm x 50mm	16.0mm	•	•	50mm	12mm
16.0mm x 65mm	20.0mm	•	•	65mm	16mm
20.0mm x 80mm	25.0mm	•		80mm	20mm

Drop In Anchors - Hollow Set CFDIA...



Hollow Set Drop In anchors are designed for anchoring into hollow concrete block. Conventional anchors will not function properly in material 25mm or less. The design of the Hollow Set Drop In Anchor overcomes this problem because the expansion sleeve length is sized to be compatible with the outer wall thickness of most hollow block.

- Large radial bearing area which reduces the amount of compression force applied to the base material during the expansion process.
- Tapered expansion sleeve.
- Serrated expansion cone.

Diameter	Drill Diameter	Yellow Zinc	Stainless Steel	Minimum Hole Depth	Thread Size
10.0mm	16.0mm	•	•		10mm
12mm	20.0mm	•	•		12mm